



PETROGREASE HT

DESCRIPTION

PETROGREASE HT is a bentonite-thickened, non-melt type grease with colloidal graphite exhibiting superior resistance to high temperature.

PROPERTIES

- Possesses high load carrying capability
- Excellent resistance to water washing
- Non-melting

TYPE

- Bentonite-thickened, non-melt type high temperature grease

APPLICATIONS

- Mining machines such as mobile drills, compressors, loaders and shuttle cars
- Steel mills, glass and rubber plants

GRADES

- NLGI Nos. 1 and 2

AVAILABLE PACKAGES

- 400-lb (181 kg) drums
- 35-lb (16 kg) pails

TYPICAL CHARACTERISTICS

| | HT 1 | HT 2 |
|---|----------------|----------------|
| Appearance/Texture | Uniform/Smooth | Uniform/Smooth |
| Color, Visual | Black | Black |
| Worked Pen. at 25°C, 100g, 5 secs., mm/10 | | |
| 60 strokes | 322 | 269 |
| 10,000 strokes | 327 | 280 |
| Tilted Wheel Bearing Test | | |
| Slump Rating | Pass | Pass |
| Leakage in grams | 2.3 | 2.3 |
| Dropping Point, °C | Non-melt | Non-melt |
| Base oil Viscosity, cSt at 40°C | 460 | 460 |