



# PETROMAR XC 2000 SERIES

## DESCRIPTION

**Petromar XC 2000 SERIES** is a 20 BN (base number) oil especially designed for the lubrication of new generation and highly rated trunk piston diesel engines in severe service burning residual fuels. Petromar XC oils are formulated to tolerate contamination with residual fuel, as experienced in some installations, without deterioration of its excellent anti-wear properties and viscosity control while maintaining superior engine cleanliness.

## PROPERTIES

- Exhibits API engine service classification of CF performance
- Provides improved fuel solubility for exceptional engine cleanliness
- Offers improved oxidation resistance and very good viscosity control
- Provides superior protection against piston deposits and ring sticking
- Possesses excellent water shedding characteristics for effective removal of water contaminant by centrifuging

## APPLICATION

- Petromar XC 2000 SERIES is suitable for use in diesel engines using fuels with 1.5%-2.5% sulfur and requiring 20 BN oil.

## GRADES

- SAE 30 and 40

## AVAILABLE PACKAGES

- 200-liter drums
- 18-liter pails

## TYPICAL CHARACTERISTICS

	2030	2040
Density at 15°C, kg/L	0.9042	0.8979
Viscosity at 40°C, cSt	106.4	148.0
Viscosity at 100°C, cSt	12.00	14.85
Viscosity Index	102	100
TBN, mg KOH/g	21.0	21.0
Flash Point, COC, °C	236	244
Pour Point, °C	-6	-6